



URSA[®] LA-3

SAE 30, 50

PRODUCT DESCRIPTION

Ursa LA-3 SAE 30 and 50 are monograde oils for use in transmissions operating in all service conditions.

CUSTOMER BENEFITS

Ursa LA-3 SAE 30 and 50 provide:

- **Low wear** - delivering long parts life to all components and low maintenance costs.
- **High cleaning power** - its detergent and dispersant characteristics help to keep the systems free of sludge and varnish.
- **Long life to seals** - its balanced formulation is compatible with most materials used in the manufacture of seals.

APPLICATIONS

Ursa LA-3 SAE 30 and 50 in viscosities defined by manufactures can be used in transmissions, final drives and hydraulic systems, where required an oil with specifications below :

Ursa LA-3 SAE 30 and 50 are appropriate when required:

- **Fluid transmissions requirements**
 - Allison C-4 (SAE 30)
 - Minimum 12 FZG

Product(s) manufactured in Brazil.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 Jan 2015

©2007-2015 Chevron U.S.A. Inc. All rights reserved.

Chevron, Texaco Logo Star and Ursa are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

TYPICAL TEST DATA

SAE Grade	ASTM Method	30	50
<i>Product Number</i>	-	237321	237323
<i>MSDS Number</i>	-	11801BRA	11801BRA
Density at 20°C	D4052	0.8907	0.8985
Viscosity, Kinematic cSt at 40°C cSt at 100°C	D445 D445	92.67 10.92	212.1 19.06
Viscosity Index	D2270	99	101
Flash Point, COC, °C	D92	246	256
Pour Point, °C	D97	-24	-12

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.